



Shandong lehang Bearing Co., Ltd

0.669 Inch | 17 Millimeter x 1.079 Inch | 27.4 Millimeter x 1.189 Inch | 30.2 Millimeter TIMKEN YAS 17 Pillow Block Bearings



Bearing No. YAS 17

YAS 17 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	0.48
EAN	0087796169593
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	10 Millimeter
Relubricatable	Yes
Insert Part Number	GYE17KRRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Metric
Other Features	Single Row Spherical Normal Duty High Base
Long Description	2 Bolt Pillow Block; 17MM Bore; 30.2MM Base to Center Height; Set Screw Mount; Ball Bearing;



Shandong lehang Bearing Co., Ltd

	69.8MM Minimum Bolt Spacing; 114.3MM Bolt Spacing Maximum; Relubricatable; Cast Iron; Double Land Riding Ru
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	YAS 17
Weight / LBS	1.05
d	0.669 Inch 17 Millimeter
Bolt Spacing Minimum	2.748 Inch 69.8Millimeter
Bolt Spacing Maximum	4.5 Inch 114.3Millimeter
D	1.079 Inch 27.4 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Nominal Bolt Center to Center	3.8 Inch 97 Millimeter
B	1.189 Inch 30.2 Millimeter
Shaft Size d	0.669 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	0.941 in
Dimension T	0.594 in
Dimension D1	0.902 in
Series	Industrial
Weight	1.0 lb
Seal Type	Shroud Seal
Base to Center Height H	30.16 mm
Total Length L	123.8 mm
Total Width A	1.189 in



Shandong lehang Bearing Co., Ltd

Bolt Hole Spacing J	92.1 mm
Bolt Hole Width N	11.1 mm
Bolt Hole Length N1	22.2 mm
Foot Height H1	11.9 mm
Total Height H2	56.4 mm
Dimension L1	41.3 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	11.5 mm
Dimension B1	1.079 in
Static Load Rating	1070 lbf
Dynamic Load Rating	2380 lbf